



# EOS 1500D

STEP UP TO DSLR PHOTOGRAPHY

**Canon**

# EOS 1500D DSLR

Discover the perfect entry level DSLR, EOS 1500D.  
Shoot and share DSLR quality images with ease straight out the box  
and share instantly via Canon Camera Connect App

**24.1** MEGA  
PIXELS  
CMOS

Crisp, clean images with  
incredible image quality  
that you will be proud to  
hang on your walls

  
Feature Guide

Learn how to  
take fantastic shots  
from day one with  
built-in feature guide

  
EOS Movie  
FULL HD

Make movie magic  
and capture special  
moments with  
Full HD movies

  
Creative Filter

Add your own twist with  
a range of built-in  
creative filters including  
miniature effect

**3.0"**   
 LCD

Frame your shot and  
review your image on  
the high resolution  
3" LCD screen



Get social in seconds  
and post your quality  
images with the Canon  
Camera Connect app

 **CameraAssist**

Get the most out of your new Canon camera  
Find out more: [canon.com.au/cameraassist](http://canon.com.au/cameraassist)

*no one sees it like you*

**Canon**

# TECHNICAL SPECIFICATIONS

# EOS 1500D

<b>IMAGE SENSOR</b>	Type Effective Pixels Total Pixels Aspect Ratio Low-Pass Filter Sensor Cleaning Colour Filter Type	Approx. 22.3 mm x 14.9 mm CMOS Approx. 24.1 megapixels Approx. 24.7 megapixels 3:2 Built-in/Fixed Manual cleaning and Dust Delete Data acquisition Primary Colour	<b>EXPOSURE CONTROL</b>	<b>Metering modes</b>	Via optical viewfinder:  Evaluative via 63 zone dual-layer metering sensor (linked to all AF points) Partial (centre, approx. 10% of viewfinder) Centre-weighted average available  Via live view on LCD screen:  Evaluative metering (315 zones)  Via optical viewfinder:  EV 1-20 (at room temperature, ISO 100, evaluative metering)  Via live view on LCD screen:  EV 0-20 (at room temperature, ISO 100, evaluative metering)  Auto: In 1-shot AF mode with evaluative metering exposure is locked when focus is achieved.  Manual: By AE lock button in creative zone modes. +/- 5 EV in 1/3 or 1/2 stop increments (can be combined with AEB). 3 shots +/- 2 EV, 1/2 or 1/3-stop increments AUTO (100-6400), 100-6400 in 1-stop increments ISO can be expanded to H: 12800  During Movie shooting: Auto (100-6400), 100-6400 (Whole stop increments)
<b>IMAGE PROCESSOR</b>	Type	DIGIC 4+	<b>Metering Range</b>	<b>AE Lock</b>	
<b>LENS</b>	Lens Mount Focal Length Image Stabilisation	EF/EF-S Equivalent to 1.6x the focal length of the lens Optical Image Stabilizer on compatible lens	<b>Exposure Compensation</b>	<b>AEB</b>	<b>ISO Sensitivity</b>
<b>FOCUSING</b>	Type	Via optical viewfinder:  TTL secondary image-forming phase-difference detection system with AF-dedicated sensor  Via live view on LCD screen:  Contrast detection AF Via optical viewfinder:  9 AF points (f/5.6 cross-type at centre) Via optical viewfinder:  Centre AF point: EV 0-18 (at room temperature & ISO 100) Other AF points: EV 1-18 (at room temperature & ISO 100)  Via live view LCD screen:  EV 1-18 (at room temperature & ISO 100) Via optical viewfinder:  AI Focus (Switches between One-Shot AF and AI SERVO AF automatically) One Shot AF AI Servo Manual  Via live view LCD screen:  One Shot AF (Contrast detect AF) Quick Mode (via phase detection AF sensor) Manual Via optical viewfinder:  Automatic selection from up to 9 points Manual selection  Via live view on LCD screen:  FlexiZone - Freely position 1 AF point via manual selection Live Mode - Automatic selection with face detection Indicated by superimposed display in the viewfinder and on the LCD monitor	<b>SHUTTER</b>	<b>WHITE BALANCE</b>	<b>Custom White Balance</b>
<b>AF System/ Points</b>	AF working range		<b>Type</b>	<b>Settings</b>	<b>WB Bracketing</b>
<b>AF Modes</b>	AF Point Selection		<b>Speed</b>		
<b>Selected AF point display</b>	Predictive AF AF Lock		<b>VIEWFINDER</b>	<b>Type</b>	<b>Coverage (Vertical/Horizontal)</b>
<b>AF Assist Beam</b>	Manual Focus		<b>Magnification</b>	<b>Eyepoint</b>	<b>Dioptr Correction</b>
<b>Manual Focus</b>			<b>Focusing Screen</b>	<b>Mirror</b>	<b>Depth of field preview</b>
<b>Manual Focus</b>			<b>Eye-piece shutter</b>	<b>LCD MONITOR</b>	<b>Type</b>
<b>Manual Focus</b>			<b>Depth of field preview</b>	<b>Coverage</b>	<b>Viewing Angle (horizontally/vertically)</b>
<b>Manual Focus</b>			<b>Eye-piece shutter</b>	<b>Brightness Adjustment</b>	<b>Display Options</b>
<b>Manual Focus</b>			<b>Depth of field preview</b>	<b>Quick Control</b>	<b>Screen Camera settings</b>

no one sees it like you

Canon

# TECHNICAL SPECIFICATIONS

# EOS 1500D

## FLASH

**Built-in Flash GN (ISO 100, meters)**

**Built-in Flash Coverage**

**Built-in Flash recycle time**

**Modes**

**Red-Eye Reduction**

**X-sync**

**Flash Exposure Compensation**

**Flash Exposure Lock**

**Second Curtain Synchronisation**

**HotShoe/ PC terminal**

**External Flash Compatibility**

**External Flash Control**

9.2

up to 17mm focal length (35mm equivalent: 28mm)

Approx. 2 seconds

Auto, Manual Flash On/off

Yes - with red eye reduction lamp

X-contact not equipped, Max. flash sync speed:

1/200 sec. with compatible Speedlites

+/- 2EV in 1/2 or 1/3 increments

Yes

Yes

Yes

Yes/No

E-TTL II with EX series Speedlites<sup>[32]</sup>

Available via camera menu screen, except for

wireless radio flash shooting settings

## SHOOTING

**Modes**

Scene Intelligent Auto, No Flash, Creative Auto, Portrait, Landscape, Close-up, Sports, Food, Night Portrait, Movie, Program AE, Shutter priority AE, Aperture priority AE, Manual

**Picture Styles**

Auto, Standard, Portrait, Landscape, Neutral, Faithful Monochrome, User Defined (x3)

**Colour Space**

sRGB and Adobe RGB

**Image Processing**

Highlight Tone Priority  
Auto Lighting Optimizer (4 settings)  
Long exposure noise reduction  
High ISO speed noise reduction (4 settings)  
Auto Correction of Lens Peripheral illumination (up to 36 lens profiles can be registered in camera)

**Drive modes**

Creative filters (Grainy B/W, Soft focus, Toy camera, Miniature effect, Fish-eye) - during image playback only  
Single, Continuous, Self timer (2s, 10s, 10s + continuous shots 2-10)

**Continuous Shooting**

Max. Approx. 3 fps for approx. 150 JPEG images<sup>[1]</sup>, 11 images RAW<sup>[2] [10]</sup>

## LIVE VIEW MODE

**Coverage**

**Frame Rate**

**Focusing**

Approx. 100% (horizontally and vertically)

29.97 fps

Live Mode: One Shot AF (Contrast detect AF)

Quick Mode: One Shot AF (phase detection AF sensor)

Manual (Magnification 5x or 10x available)

**Metering**

Real-time evaluative metering with image sensor

Active metering time can be changed

**Display Options**

Grid overlay (x2), Histogram

## FILE TYPE

**Still Image Type**

JPEG: Fine, Normal (Exif 2.30 compliant) / Design rule for Camera File system (2.0),  
RAW: RAW (14bit, Canon original RAW 2nd edition), Digital Print Order Format [DPOF] Version 1.1 compliant

**RAW+JPEG simultaneous recording**

Yes, RAW + Large JPEG

**Image Size**

JPEG 3:2: (L) 6000 x 4000, (M) 3984 x 2656, (S1) 2976 x 1984, (S2) 1920 x 1280, (S3) 720 x 480  
JPEG 4:3: (L) 5328 x 4000, (M) 3552 x 2664, (S1) 2656 x 1992, (S2) 1696 x 1280, (S3) 640 x 480  
JPEG 16:9: (L) 6000 x 3368, (M) 3984 x 2240, (S1) 2976 x 1680, (S2) 1920 x 1080, (S3) 720 x 408  
JPEG 1:1: (L) 4000 x 4000, (M) 2656 x 2656, (S1) 1984 x 1984, (S2) 1280 x 1280, (S3) 480 x 480

**Movie Type**

RAW: (RAW) 6000 x 4000  
MOV (Video: H.264 inter frame (IPB), Sound: Linear PCM, recording level can be manually adjusted by user) 1920

**Movie Size**

x 1080 (30, 25, 24 fps)  
1280 x 720 (60, 50 fps)  
640 x 480 (30, 25 fps)

**Movie Length**

Max duration 29 min 59 sec, Max file size 4 GB

**Folders**

New folders can be manually created and selected

**File Numbering**

Consecutive numbering  
Auto reset  
Manual reset

## OTHER FEATURES

**Custom Functions**

**Metadata Tag**

**Intelligent Orientation Sensor**

**Playback zoom**

**Display Formats**

**Slide Show**

**Histogram**

**Highlight Alert**

**Image Erase/Protection**

**Menu Categories**

**Menu Languages**

**GPS**

**Firmware Update**

## INTERFACE

**Computer**

**Wi-Fi**

**Wi-Fi Security**

**NFC**

**Other**

**DIRECT PRINT**

**Canon Printers**

**PictBridge**

**STORAGE**

**Type**

**SUPPORTED OPERATING SYSTEM**

**PC & Macintosh**

**SOFTWARE**

**Image Processing**

**Other**

11 Custom Functions

User copyright information (can be set in camera) Image rating (0-5 stars)

Yes

1.5x - 10x enabled in 15 steps

(1) Single image with information (2 levels)

(2) Single image

(3) Index display (4/9 images)

(4) Jump Display (1/10/100 images, by Date, by Folder, Movies only, Stills only, by Rating)

Image selection: All images, by Date, by Folder, Movies, Stills, Rating

Playback time: 1/2/3/5/10 or 20

seconds Repeat: On/Off

Transition Effect: Off, Slide 1, Slide 2, Fade 1, Fade 2,

Fade 3

Background Music: On, Off

Brightness

: Yes

RGB: Yes

Yes

Erase: Single image, selected images, all images

in folder or all images on card

Protection: Erase protection for single image,

all images in a folder or all images in the card

(1) Shooting menu (x4)

(2) Playback menu (x2)

(3) Setup menu (x3)

(4) My Menu

25 Languages

English, German, French, Dutch, Danish,

Portuguese, Finnish, Italian, Norwegian, Swedish,

Spanish, Greek, Russian, Polish, Czech, Hungarian,

Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified

Chinese, Traditional Chinese, Korean and Japanese

Compatible with GPS receiver GP-E2

Update possible by the user.

Hi-Speed USB

Wi-Fi (IEEE 802.11 b/g/n), (2.4 GHz only)<sup>[17]</sup>

Connectivity to Smart devices is possible via Canon

Camera Connect app<sup>[34]</sup>

Camera Access Point: WPA2-PSK with AES

encryption or open

Infrastructure: Shared key, with WEP

encryption, WPA-PSK/WPA2-PSK with TKIP/AES

encryption or

open

NFC connectivity is possible only with

compatible Canon or Android devices.

HDMI mini (Type-C) output

Canon Compact Photo Printers and PIXMA

Printers supporting PictBridge

Yes

SD card, SDHC card or SDXC card

Windows 10 / 8.1 / 7 SP1<sup>[24]</sup>

Mac OS X 10.10 - 10.13

Digital Photo Professional (RAW Image Processing)

EOS Utility

EOS Lens Registration Tool

EOS Web Service Registration

Tool EOS Sample Music

Picture Style Editor

Camera Connect app available on iOS and Android

devices<sup>[34]</sup>

no one sees it like you

Canon

# TECHNICAL SPECIFICATIONS

# EOS 1500D

## POWER SOURCE

### Batteries

1 x Rechargeable Li-ion Battery LP-E10

### Battery life

Approx. 500 (at 23°C, AE 50%, FE 50%) <sup>[5]</sup>

Approx. 410 (at 0°C, AE 50%, FE 50%)

### Battery Indicator

4 levels

### Power saving

Power turns off after 30sec or 1, 2, 4, 8 or 15mins.

### Power Supply & Battery

### Chargers

Battery charger LC-E10E

Compact power adaptor CA-PS700, DC coupler DR-E10

## PHYSICAL SPECIFICATIONS

### Body Materials

Polycarbonate resin with glass fibre & special conductive fibre

### Operating Environment

0 – 40 °C, 85% or less humidity

### Dimensions (WxHxD)

129.0 x 101.3 x 77.6mm

### Weight (body only)

Approx. 475 g (CIPA testing standard, including battery and memory card)

## ACCESSORIES

### Viewfinder

Eyecup Ef

Rubber Frame Ef

E-series Dioptic Adjustment Lenses

Eye-piece Extender EP-EX15II

Angle Finder C

Magnifier MG-Ef

### Case

Semi Hard Case EH26-L, EH27-L

Protecting Cloth PC-E1, PC-E2

Shoulder Bag SB10, SB100

Backpack BP10, BP12, BP100

Messenger Bag MS10, MS11

Sling Bag SL100

Holster HL100

### Lenses

All EF and EF-S lenses

### Flash

Canon Speedlites (270EX II, 430EX III-RT, 600EX II-RT, Macro-Ring-Lite MR-14EX II, Macro Twin Lite MT-26EX-RT, Speedlite Transmitter ST-E2, Speedlite Transmitter ST-E3-RT) <sup>[6]</sup>

### Remote Controller/ Switch

Remote Switch RS-60E3,

Timer Remote Controller TC-80N3 via Remote

Controller Adapter RA-E3

### Other

Hand Strap E2, GPS Receiver GP-E2, HDMI Cable

HTC-100, Interface Cable IFC400PCU

All data is based on Canon standard testing methods except where indicated.

Subject to change without notice.

<sup>[1]</sup> Large/Fine (Quality 8) resolution

<sup>[2]</sup> Based on Canon's testing conditions, JPEG, ISO 100, Standard Picture Style. Varies depending on the subject, memory card brand and capacity, image recording quality, ISO speed, drive mode, Picture Style, Custom functions etc.

<sup>[4]</sup> With 50mm lens at infinity, -1m<sup>-1</sup> dpt

<sup>[5]</sup> Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated

<sup>[6]</sup> Recommended Exposure Index

<sup>[10]</sup> Sustained continuous shooting speed is tested based on Canon's testing standard.

Function requires compatible SDHC/SDXC UHS Speed Class 1 memory card, total number of frames captured varies depending on shooting subject, settings and brand of memory card

<sup>[17]</sup> Wi-Fi use may be restricted in certain countries or regions.

<sup>[24]</sup> Software applications compatible with Windows 10 in Windows 10 Desktop Mode only

<sup>[32]</sup> Speedlites other than the EX-series or non-Canon flash units cannot be used. Not all functions of the Canon EX-series flashes are supported.

<sup>[34]</sup> Canon Camera Connect app is available for Apple iOS and Android devices only. Please refer to Google PlayStore® and Apple AppStore® for compatible versions of Android OS and Apple iOS.

